



Specification

LCD Touch Panel

LCD Size	15" (4 : 3 ratio)
Brightness	250 nits or 1000+ nits (Optional)
Resolution	1024 x 768
Colors	16.7M
Active Area	337.920 (H) x 270.336 (V) (mm)
Pixel Pitch	0.264 x 0.264 (mm)
Viewing Angle	80/80 (H), 80/80 (V)
Contrast Ratio	1000 : 1
LED Life Time	50,000 Hrs
Touch Screen	True-Flat PCAP (10 Points)
Surface Hardness	7H
Surface type	Non-reflective surface

External I/O Ports

Display Input	VGA/HDMI
Display Control	OSD

Audio

Internal Speaker	(Optional)
------------------	------------

Power

Power Supply	DC IN 12V or 9 - 36V (Optional)
--------------	---------------------------------

Environment

Ventilation	Fanless
Dust & Water Proof	Full IP69K/IP68 Stainless steel SUS304 or SUS316, true flat PCAP Touch design
Operating Temperature	0°C ~ 60°C (32~140°F)
Storage Temperature	-20°C ~ 70°C (-4~176°F)
Humidity	10% ~ 95% R/H non-condensing

Dimensions (WxDxH)

400 x 325 x 58 mm

Weight

5.5 kg

Mounting

VESA Mount 100 x 100 mm

