



Specification

| | | |
|---------------------------|--|---|
| LCD Touch Panel | LCD Size | 15.6" |
| | Brightness | 400 nits or 1000/1500 nits (Optional) |
| | Resolution | 1920 x 1080 |
| | Colors | 16.7M |
| | Viewing Angle | 89/89 (H), 89/89 (V) |
| | Contrast Ratio | 3000 : 1 |
| | LED Life Time | 30,000 Hrs |
| Touch Screen | PCAP Touch or Resistive Touch (Optional) | |
| External I/O Ports | Display Input | VGA + DP + HDMI or VGA + DVI |
| | Display Control | OSD Key Control |
| Audio | Internal Speaker | Speaker header x 1 |
| Power | Power Supply Connector | 12V/60W Power adapter or 9-36V wide range input with phoenix connector (Optional) |
| Environment | Ventilation | Fanless |
| | Dust & Water Proof | Open frame front, with Gasket for water proof (Optional) |
| | Operating Temperature | -20°C ~ 50°C |
| | Storage Temperature | -25°C ~ 55°C |
| Humidity | 5% ~ 95% RH non-condensing | |
| Dimensions (WxDxH) | 391.4 x 241.7 x 42.5 mm | |
| Weight | 4.0 kg | |
| Mounting | Open Frame Mount | |

