



Specification

LCD Touch Panel	LCD Size	15" (4:3)
	Brightness	250 nits or 1000+ nits (Optional)
	Resolution	1024 x 768
	Colors	16.7M
	Active Area	337.920 (H) x 270.336 (V) (mm)
	Pixel Pitch	0.264 x 0.264 (mm)
	Viewing Angle	80/80 (H), 80/80 (V)
	Contrast Ratio	1000 : 1
	LED Life Time	50,000 Hrs
	Touch Screen	True-Flat PCAP (10 Points)
	Surface Hardness	7H
	Surface type	Non-reflective surface
External I/O Ports	Display Input	HDMI (with 2-meter M19 waterproof HDMI cable)
	USB	USB (with 2-meter M19 waterproof USB Touch cable)
	Display Control	OSD
Audio	Internal Speaker	(Optional)
Power	Power Supply	DC IN 12V with 2-meter M12 waterproof power cable with 60W power adapter or 9 - 36V wide range (Optional)
Environment	Ventilation	Fanless
	Dust & Water Proof	Full IP69K/IP68 Stainless steel SUS304 or SUS316, true flat PCAP Touch design
	Operating Temperature	0°C ~ 60°C (32~140°F)
	Storage Temperature	-20°C ~ 70°C (-4~176°F)
	Humidity	10% ~ 95% R/H non-condensing
Dimensions (WxDxH)		378 x 301 x 53.2 mm
Weight		5.5 kg
Mounting		VESA Mount 100 x 100 mm

