



Specification

LCD Touch Panel	LCD Size	10.1" (16:10 ratio)
	Brightness	350 nits or 1000+ nits (Optional)
	Resolution	1280 x 800
	Colors:	16.7M
	Active Area	216.96 (H) x 135.6 (V) (mm)
	Pixel Pitch	0.1695 x 0.1695 (mm)
	Viewing Angle	85/85 (H), 85/85 (V)
	Contrast Ratio	800 : 1
	LED Life Time	25,000 Hrs
	Touch Screen	True-Flat PCAP Touch or Resistive Touch (Optional)
	Surface Treatment	Anti-UV, Anti-IR protection (Optional)
	Optical Bonding	Support (Optional)
External I/O Ports	Display Input	HDMI (with 2-meter M19 waterproof HDMI cable)
	USB	USB (with 2-meter M19 waterproof USB Touch cable)
	Display Control	OSD
Audio	Internal Speaker	(Optional)
Power	Power Supply	DC IN 12V with 2-meter M12 waterproof power cable with 60W power adapter or 9 - 36V wide range (Optional)
Environment	Ventilation	Fanless
	Dust & Water Proof	Full IP69K/IP68 Stainless steel SUS304 or SUS316, true flat PCAP Touch design
	Operating Temperature	0°C ~ 60°C (32~140°F)
	Storage Temperature	-20°C ~ 70°C (-4~176°F)
	Humidity	10% ~ 95% R/H non-condensing
Dimensions (WxDxH)		276 x 190 x 51.2 mm
Weight		4.5 kg
Mounting		VESA Mount 75 x 75 mm

