



Specification

LCD Touch Panel

LCD Size	15.6"
Brightness	400 nits or 1000+ nits (Optional)
Resolution	1920 x 1080
Colors	16.7M
Viewing Angle	88/88 (H), 85/85 (V)
Contrast Ratio	1000 : 1
LED Life Time	50,000 Hrs
Touch Screen	True-Flat PCAP Touch or Resistive Touch (Optional)
Surface Treatment	Anti-UV, Anti-IR protection (Optional)
Optical Bonding	Support (Optional)

External I/O Ports	Display Input	HDMI (with 2-meter M19 waterproof HDMI cable)
	USB	USB (with 2-meter M19 waterproof USB Touch cable)
	Display Control	OSD
Audio	Internal Speaker	(Optional)
Power	Power Supply	DC IN 12V with 2-meter M12 waterproof power cable with 60W power adapter or 9 - 36V wide range (Optional)
Environment	Ventilation	Fanless
	Dust & Water Proof	Full IP69K/IP68 Stainless steel SUS304 or SUS316, true flat PCAP Touch design
	Operating Temperature	0°C ~ 60°C (32~140°F)
	Storage Temperature	-20°C ~ 70°C (-4~176°F)
	Humidity	10% ~ 95% R/H non-condensing
Dimensions (WxDxH)	416 x 266 x 51.2 mm	
Weight	5.5 kg	
Mounting	VESA Mount 100 x 100 mm	

