



Specification

LCD Touch Panel	LCD Size	23.8"
	Brightness	250 nits or 1000+ nits (Optional)
	Resolution	1920 x 1080
	Colors:	16.7M
	Active Area	527.04 (H) x 296.46 (V) (mm)
	Pixel Pitch	274.5 x 274.5 (um)
	Viewing Angle	89/89 (H), 89/89 (V)
	Contrast Ratio	3000 : 1
	LED Life Time	30,000 Hrs
	Touch Screen	True-Flat PCAP Touch or Resistive Touch (Optional), Optical Bonding (Optional), Anti-UV (Optional), Anti-IR (Optional)
External I/O Ports	Surface Hardness	7H
	Surface type	AG/AR (Optional), Water rejection (Optional)
External I/O Ports	Display Input	VGA+DP+HDMI or VGA+DVI (Optional)
	Display Control	OSD
Audio	Internal Speaker	2 x 5 Watts, stereo speaker (optional)
Power	Power Supply	DC IN 12V or Universal 90-240V, 12V/50W Power adapter or DC IN 9-36V (Optional)
Environment	Ventilation	Fanless
	Dust & Water Proof	Front IP67, Aluminum front bezel, true flat PCAP touch design
	Operating Temperature	0°C ~ 60°C (32~140°F)
	Storage Temperature	-20°C ~ 70°C (-4~176°F)
	Humidity	10% ~ 95% R/H non-condensing
Dimensions (WxDxH)	574.4 x 348.8 x 50 mm	
Weight	6.0 kg	
Mounting	VESA Mount 100 x 100 mm or Panel Mount with Panel mount bracket (Optional)	

