



(These photos are for reference)
(Please refer to below spec. & drawings)

Specification

LCD Touch Panel

LCD Size	15.6"
Brightness	250 nits or 400 nits (FHD) or 1000+ nits (Optional)
Resolution	1366 x 768 or 1920 x 1080 (Optional)
Colors:	16.7M
Viewing Angle	88/88 (H) , 85/85 (V)
Contrast Ratio	1000 : 1
LED Life Time	50,000 Hrs
Touch Screen	True-Flat PCAP or Resistive Touch (Optional)
Surface Hardness	7H
Surface Treatment	Anti-UV, Anti-IR protection

External I/O Ports

Display Input	VGA + DP + HDMI
Display Control	OSD

Audio

Internal Speaker	2 x 5 Watts, internal stereo speaker (Optional)
------------------	---

Power

Power Supply	DC IN 12V or Universal 90-240V Power adapter
--------------	--

Environment

Ventilation	Fanless
Dust & Water Proof	Front IP67, Aluminum front bezel, True-Flat design
Operating Temperature	0°C ~ 60°C (32~140°F)
Storage Temperature	-20°C ~ 70°C (-4~176°F)
Humidity	10% ~ 95% R/H non-condensing

Dimensions (WxDxH)

396.8 x 247 x 38 mm

Weight

2.0 kg

Mounting

VESA Mount 100 x 100 mm, or Panel Mount with Panel Mount bracket (Optional)

