



Specification

System	Processor Chipset System Memory Storage Device Graphic Engine DIO Watchdog	Intel® Core i3-6100U Dual-core, clock speed 2.30G, TDP 15W CPU Integrated, TPM 2.0 support 1x DDR3L 1333/1600MHz SO-DIMM up to 8GB 1x 2.5" SATA HDD or SSD or mSATA module Intel HD Graphics Digital I/O 4 in/ 4 out With Watchdog Timer
LCD Touch Panel	LCD Size Brightness Resolution Touch Screen	17" (5:4 ratio) 250 nits 1280 x 1024 True-Flat PCAP Touch or Resistive Touch (Optional)
Expansion	Mini PCI-E Slot MSR	2 (1x slot co-lay with mSATA) (For Wifi module with Antenna) 2 tracks, or 3 tracks (Optional)
External I/O Ports	USB Serial Port LAN Display	4x USB (Up to 5x USB) 4x RS-232 2x LAN 1x VGA, 1xHDMI
Audio	Internal Speaker	Speaker Header x1 (Optional)
Power	Power Supply Connector	84W Power Adapter DCIN Input : 9V~28V Connector types: 1x Round Type DC Jack , 1x PHOENIX Connector
Environment	Ventilation Dust & Water Proof Operating Temperature Storage Temperature Humidity	Fanless Front IP65 , Aluminum front bezel, true flat design 0°C ~ 60°C -25°C ~ 75°C 5% ~ 95% RH non-condensing
Dimensions (WxDxH)	392.32 x 324.74 x 51 mm	
Weight	4.20 kg	
Mounting	VESA Mount 75 x 75 mm; Optional table stand (tilt 0° ~ 90°)	
OS Supported	Win7, Win 8, Win10 IOT, Linux	

