



Specification

System	Processor	Intel® Core i5-7200U Dual-Core, clock speed 2.50GHz, TDP 15W
	Chipset	CPU Integrated, TPM 2.0 support
	System Memory	1x DDR3L 1333/1600MHz SO-DIMM up to 8GB
	Storage Device	1x 2.5" SATA HDD or SSD or mSATA module
	Graphic Engine	Intel HD Graphics
	DIO	Digital I/O 4 in/ 4 out
	Watchdog	With Watchdog Timer
LCD Touch Panel	LCD Size	21.5"
	Brightness	250 nits (400 nits optional)
	Resolution	1920 x 1080
	Touch Screen	True-Flat PCAP Touch (IP67 Front)
Expansion	Mini PCIe Slot	2 (1x slot co-lay with mSATA)
	RFID Reader	Support 125 KHz & 13.56 MHz (Optional)
External I/O Ports	USB	2x USB 3.0, 2x USB 2.0 (Optional)
	Serial Port	2x RS232
	LAN	2x LAN
	Display	1x VGA, 1x HDMI
Audio	Internal Speaker	2x Stereo speaker
Power	Power Supply Connector	Power adapter DCIN Input: 9-28V, Connector type: 1x Phoenix connector
Environment	Ventilation	Fanless
	Dust & Water Proof	Front IP67
	Operating Temperature	0 ~ 60°C (32 ~ 140°F)
	Storage Temperature	-20 ~ 70°C (-4 ~ 176°F)
	Humidity	5% ~ 95% R/H, non-condensing
Dimensions (WxDxH)		537.8 x 329.3 x 55 mm
Weight		5 kg
Mounting		VESA Mount 100 x 100 mm
OS Supported		Win7, Win 8, Win10 IOT, Linux

