



Specification

System	Processor	Intel® Core i5-7200U Dual-core, clock speed 2.50G, TDP 15W
	Chipset	CPU Integrated, TPM 2.0 support
	System Memory	1x DDR3L 1333/1600MHz SO-DIMM up to 8GB
	Storage Device	1x 2.5" SATA HDD or SSD or mSATA module
	Graphic Engine	Intel HD Graphics
	DIO	Digital I/O 8 in/ 8 out
	Watchdog	With Watchdog Timer
LCD Touch Panel	LCD Size	15" (4:3 ratio)
	Brightness	400 nits
	Resolution	1024 x 768 (HD)
	Touch Screen	True-Flat PCAP Touch or Resistive Touch (Optional)
Expansion	Mini PCI-E Slot	2 (1x slot co-lay with mSATA)
External I/O Ports	USB	2x USB3.0, 2x USB2.0
	Serial Port	4x RS-232
	LAN	2x LAN
	Display	1x VGA, 1xHDMI
Audio	Internal Speaker	Speaker Header x1 (Optional)
Power	Power Supply	84W Power Adapter
	Connector	DCIN Input : 9V~28V Connector types:1x Round Type DC Jack , 1x PHOENIX Connector
Environment	Ventilation	Fanless
	Dust & Water Proof	Front IP65 ,Aluminum front bezel, true flat deign
	Operating Temperature	0°C ~ 60°C
	Storage Temperature	-25°C ~ 75°C
	Humidity	5% ~ 95% RH non-condensing
Dimensions (WxDxH)		359.1 x 281.8 x 51 mm
Weight		3.80 kg
Mounting		VESA Mount 75 x 75 mm
OS Supported		Win7, Win 8, Win10 IOT, Linux

