



### Specification

<b>LCD Touch Panel</b>	LCD Size	19" (5:4 ratio)
	Brightness	250 nits
	Resolution	1280x 1024
	Colors:	16.7M
	Active Area	376.32 (H) x 301.06 (V) (mm)
	Pixel Pitch	0.294 x 0.294 (mm)
	Viewing Angle	85/85 (H) , 80/80 (V)
	Contrast Ratio	1000 : 1
	LED Life Time	30,000 Hrs
	Touch Screen	True-Flat PCAP Touch (10 Points)
	Surface Hardness	7H
Surface type	Non-reflective surface	
<b>External I/O Ports</b>	Display Input	VGA+DP+HDMI
	Display Control	OSD
<b>Audio</b>	Internal Speaker	2 x 5 Watts, stereo speaker (internal)
<b>Power</b>	Power Supply	DC IN 12V or Universal 90-240V, 12V/50W Power adapter
<b>Environment</b>	Ventilation	Fanless
	Dust & Water Proof	Front IP67 ,Aluminum front bezel, true flat deign
	Operating Temperature	0°C ~ 60°C (32~140°F)
	Storage Temperature	-20°C ~ 70°C(-4~176°F)
	Humidity	10% ~ 95% R/H non-condensing
<b>Dimensions (WxDxH)</b>		424.5 x 349.2 x 40.5 mm
<b>Weight</b>		3.2 kg
<b>Mounting</b>		VESA Mount 75 x 75 mm and 100 x100mm

