



Specification

System	Processor Chipset System Memory Storage Device Graphic Engine DIO Watchdog	Intel Celeron Bay Trail J1900 Quad core 10W processor CPU Integrated 1x DDR3L 1333MHz SO-DIMM up to 8GB 1x 2.5" SATA HDD or SSD or mSATA module Intel HD Graphics Digital I/O 8 in/ 8 out With Watchdog Timer
LCD Touch Panel	LCD Size Brightness Resolution Touch Screen	10.1" (16:10 ratio) 350 nits 1280 x 800 (HD) True-Flat PCAP Touch or Resistive Touch (Optional)
Expansion	Mini PCI-E Slot	2 (1x slot co-lay with mSATA)
External I/O Ports	USB Serial Port LAN Display	2x USB3.0, 2x USB2.0 2x RS-232 2x LAN (1x POE-PD Optional) 1x VGA, 1xHDMI
Audio	Internal Speaker	Speaker Header x1
Power	Power Supply Connector	84W Power Adapter DCIN Input : 9V~28V Connector types: 1x Round Type DC Jack , 1x PHOENIX Connector
Environment	Ventilation Dust & Water Proof Operating Temperature Storage Temperature Humidity	Fanless Front IP65, Aluminum front bezel, true flat PCAP touch design 0°C ~ 60°C -25°C ~ 75°C 5% ~ 95% RH non-condensing
Dimensions (WxDxH)	257.2 x 170.9 x 51 mm	
Weight	2.0 kg	
Mounting	VESA Mount 75 x 75 mm	
OS Supported	Win7, Win 8, Win10 IOT, Linux	

SIDE



FRONT



BACK

