



Specification

System	Processor Chipset System Memory Storage Device Graphic Engine DIO Watchdog	Intel® Core i5-7200U Dual-core, clock speed 2.50G, TDP 15W CPU Integrated, TPM 2.0 support 1x DDR3L 1333/1600MHz SO-DIMM up to 8GB 1x 2.5" SATA HDD or SSD or mSATA module Intel HD Graphics Digital I/O 8 in/ 8 out With Watchdog Timer
LCD Touch Panel	LCD Size Brightness Resolution Touch Screen	17" (5:4 ratio) 350 nits 1280 x 1024 (HD) True-Flat PCAP Touch or Resistive Touch (Optional)
Expansion	Mini PCI-E Slot MSR Antenna	2 (1x slot co-lay with mSATA) 2 tracks, or 3 tracks (Optional) (Optional)
External I/O Ports	USB Serial Port LAN Display	2x USB3.0, 4x USB2.0 4x RS-232 2x LAN 1x VGA, 1xHDMI
Audio	Internal Speaker	Speaker Header x1 (Optional)
Power	Power Supply Connector	84W Power Adapter DCIN Input : 9V~28V Connector types: 1x Round Type DC Jack , 1x PHOENIX Connector
Environment	Ventilation Dust & Water Proof Operating Temperature Storage Temperature Humidity	Fanless Front IP65, Aluminum front bezel, true flat design 0°C ~ 60°C -25°C ~ 75°C 5% ~ 95% RH non-condensing

Dimensions (WxDxH) 392.32 x 324.74 x 52 mm, suggested Cut Out dimension is 370 x 302 mm

Weight 4.20 kg

Mounting VESA Mount 75 x 75 mm, Panel Mount bracket (Optional), Table Stand (tilt 0° ~ 90°) (Optional)

OS Supported Win7, Win 8, Win10 IOT, Linux

