



Specification

System	Processor	Intel® Core i5-7200U Dual-core, clock speed 2.50G, TDP 15W
	Chipset	CPU Integrated, TPM 2.0 support
	System Memory	1x DDR3L 1333/1600MHz SO-DIMM up to 8GB
	Storage Device	1x 2.5" SATA HDD or SSD or mSATA module
	Graphic Engine	Intel HD Graphics
	DIO	Digital I/O 8 in/ 8 out
	Watchdog	With Watchdog Timer
LCD Touch Panel	LCD Size	15" (4:3 ratio)
	Brightness	350 nits
	Resolution	1024 x 768
	Touch Screen	True-Flat PCAP Touch or Resistive Touch (Optional)
Expansion	Mini PCI-E Slot	2 (1x slot co-lay with mSATA)
	MSR	2 tracks, or 3 tracks (Optional)
	Antenna	(Optional)
External I/O Ports	USB	2x USB3.0, 4x USB2.0
	Serial Port	4x RS-232
	LAN	2x LAN
	Display	1x VGA, 1x HDMI
Audio	Internal Speaker	Speaker Header x1 (Optional)
Power	Power Supply	84W Power Adapter
	Connector	DCIN Input : 9V~28V Connector types: 1x Round Type DC Jack , 1x PHOENIX Connector
Environment	Ventilation	Fanless
	Dust & Water Proof	Front IP65, Stainless Steel front bezel (SUS304 or SUS316), true flat design
	Operating Temperature	0°C ~ 60°C
	Storage Temperature	-25°C ~ 75°C
	Humidity	5% ~ 95% RH non-condensing

Dimensions (WxDxH) 403.5 x 326.53 x 49.5 mm, suggested Cut Out dimension is 379 x 302 mm

Weight 3.5 kg

Mounting VESA Mount 75 x 75 mm, Panel Mount bracket (Optional)

OS Supported Win7, Win 8, Win10 IOT, Linux

